

## SECURITHERM shower panel

Ref. H963615

Sequential thermostatic mixer

### DESCRIPTION




#### SECURITHERM shower panel - Ref. H963615

Aluminium powder-coated SECURITHERM sequential thermostatic shower panel for wall-mounted, exposed installation.

- Top inlets with M1/2" stopcocks.
- SECURITHERM sequential thermostatic mixer (non-time flow).
- Temperature control from cold water up to 39°C.
- Maximum temperature limiter set at 39°C, can be adjusted.
- Anti-scalding failsafe: Hot water supply shuts-off immediately if cold water supply fails (and vice versa).
- Thermal shocks are possible.
- Flow rate set at 9 lpm at 3 bar.
- Sliding handset on chrome-plated rail with flexible shower hose.
- Hygiene control lever L. 100mm.
- Copper inlets.
- Concealed fixings and filters.
- 10-year warranty.





### TECHNICAL FEATURES

#### SECURITHERM shower panel - Ref. H963615

Connector	M1/2", Ø 15mm
Technology	SECURITHERM single control thermostatic mixer
Height	1050mm
Width	210mm
Flow rate	9 lpm
Temperature limiter	39°C
Finish	Aluminium
Standards and certifications	 
Warranty	



### ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  No non-return valves on inlets
-  Thermostatic: total temperature stability
-  Aluminium panel

