



### Screw Fixing Cable Tie Mounts

#### • Q-mount Series CTQM


The "2-way" mounting bases CTQM provide a safe guiding of cables and conduits.

- For cable ties up to 5 mm width
- The base is mounted with a screw with countersunk head (max.  $\varnothing$  of head: 8.0mm)

The Q-mount offers a perfect solution in combination with the Q-tie cable ties. It keeps the inserted cable tie in place during pre-assembly and ensures that the Q-tie does not slip out even in difficult situations, for example vertical mounting positions.



Q-mount, CTQM 2-way entry, screwable.



Mounting base CTQM

| Material Data         |   |
|-----------------------|---|
| Material              | Polyamide 6.6 (PA66)                              |
| Colour                | Natural (NA), Black (BK)                          |
| Operating Temperature | -40 °C to +105 °C Continuous, (+105 °C for 500 h) |
| Flammability          | UL94 V2   |



Please find more Q-Series products for your system solution on page 81 and 508.

Technical Table

| Article-No. | Type  | Length (L) | Width (W) | Height (H) | Fixing Hole $\varnothing$ (FH) | Strap Width max. (G) | Material | Colour       |
|-------------|-------|------------|-----------|------------|--------------------------------|----------------------|----------|--------------|
| 151-10920   | CTQM5 | 21.0       | 9.5       | 6.7        | 4.5                            | 5.0                  | PA66     | Natural (NA) |
| 151-10930   | CTQM5 | 21.0       | 9.5       | 6.7        | 4.5                            | 5.0                  | PA66     | Black (BK)   |

All dimensions in mm. Subject to technical changes.