

Item	Qty.	Quotation ref.	Type	Drawing / Mark
10	1	BG-240811	T.T. UXL- 7 REL6300:V3/100:V3-100:V3V	4282806 / @

SPECIFICATIONS
General Specifications

Service:	INDOOR
Insulation level	7,2 / 18,00 / 60,00 KV
Standar:	UNE EN 60044-2/2002
Frequency:	50 HZ

Technical Data

No of poles	1,00
Ratio	6300:V3 / 100:V3 - 100:V3
Primary voltage (V)	6300:V3 V
Secondary 1	100:V3 V 30 VA 1
Secondary 2	100:V3 V 30 VA 0,5
Secondary 3	
Secondary 4	
Secondary 5	
Simultaneous Burdens	2 SIMULTANEOUS SECONDARIES
Thermal Burden	VAM
Voltage Factor	1.9Un/8h

Item	Qty.	Quotation ref.	Type	Drawing / Mark
20	1	BG-240811	T.I. ACF-12 REL400/5-5-5A	4282292 / A

SPECIFICATIONS
General Specifications

Service	INDOOR
Insulation level	7,2 / 20,00 / 60,00 KV
Standard	IEC 61869-2/2012-
Frequency	50 HZ

Technical Data

Ratio	400 / 5 - 5 - 5 A
Secondary 1	5 A 30 VA 0.5 FS 5
Secondary 2	5 A 30 VA 0.5 FS 5
Secondary 3	5 A 30 VA 5P10
Secondary 4	
Secondary 5	
Overload	120,00 %
Thermal current	32 kA / 1,00 S
Dynamic Current	80,00 KA