

INTERPUMP GROUP





series

High Temperature

Special Series

PUMPS LISTED ACCORDING TO VOLUME

TABELLE POMPES ORDONNÉES SUIVANT LE DÉBIT

PUMPENTABELLE NACH FÖRDERLEISTUNG ANGEORDNET

TABLA DE BOMBAS EN ORDEN DE CAUDAL

TABELLA POMPE IN ORDINE DI PORTATA

Flow rate Débit Förderleistung Caudal Portata		r.p.m. tr./min. u.p.m. r/min.	Pressure Pression Druck Presión Pressione		MOD.	pag.
l/min.	G.P.M. (USA)	g/min.	bar	p.s.i.		
11	2.9	1450	140	2030	HT6311	54
13	3.43	1450	170	2465	HT6313	54
15	3.96	1750	140	2030	HT6315	54
		1450	160	2320	HT4715	54
18	4.75	1450	160	2320	HT4718	54
21	5.55	1450	140	2030	HT4721	54
23	6.07	1450	160	2320	HT4723	54
28	7.4	1750	250	3600	HT6628	54
39	10.3	1750	200	2900	HT6639	54
46	12.15	1750	170	2465	HT6646	54
68	18	1000	80	1160	HT6968	54
80	21.1	1000	100	1450	HT7680	54

PUMPS LISTED ACCORDING TO PRESSURE

TABELLE POMPES ORDONNÉES SUIVANT LA PRESSION

PUMPENTABELLE NACH DRUCK ANGEORDNET

TABLA DE BOMBAS EN ORDEN DE PRESIÓN

TABELLA POMPE IN ORDINE DI PRESSIONE

Pressure Pression Druck Presión Pressione		r.p.m. tr./min. u.p.m. r/min.	Flow rate Débit Förderleistung Caudal Portata		MOD.	pag.
bar	p.s.i.	g/min.	l/min.	G.P.M. (USA)		
80	1160	1000	68	18	HT6968	54
100	1450	1000	80	21.1	HT7680	54
		1450	11	2.9	HT6311	54
		1450	21	5.55	HT4721	54
140	2030	1750	15	3.96	HT6315	54
		1450	15	3.96	HT4715	54
160	2320	1450	18	4.75	HT4718	54
		1450	23	6.07	HT4723	54
170	2465	1450	13	3.43	HT6313	54
		1750	46	12.15	HT6646	54
200	2900	1750	39	10.3	HT6639	54
250	3600	1750	28	7.4	HT6628	54





series

High Temperature

For car wash and industrial applications up to 85°C (185°F)
 Pour car wash et applications industrielle jusqu'à 85°C (185°F)
 Für car wash und industrielle Einsätze bis 85°C (185°F)
 Para car wash y aplicaciones industriales hasta 85°C (185°F)
 Per car wash e applicazioni industriali fino a 85°C (185°F)



Pump type Type de pompe Pumpentype Tipo de bomba Tipo di pompa	Flow rate Débit Förderleistung Caudal Portata		Max. pressure Pression Druck Presión Pressione		r.p.m. tr./min. u.p.m. r/min. g./min.	Power Puissance Leistung Potencia Potenza		Weight Poids Gewicht Peso Peso	Dimensions Dimensions Dimension Dimensiones Dimensioni
	l/min.	G.P.M. (U.S.A.)	bar	p.s.i.		kW	hp		

63.HT series	HT6311	11	2.9	140	2030	1450	2,94	4	8,15	213,5x211x119,5
	HT6313	13	3.43	170	2465		4,04	5,5		
	HT6315	15	3.96	140	2030	1750	4,04	5,5	8,15	213,5x211x119,5

47.HT series	HT4715	15	3.96	160	2320	1450	4,56	6,2	14,5	315,5x254,5x146
		10	2.64	160	2320	950	3,05	4,15		
	HT4718	18	4.75	160	2320	1450	5,51	7,5		
		12	3.17	160	2320	950	3,67	4,99		
	HT4721	21	5.55	140	2030	1450	5,51	7,5		
		17	4.5	160	2320	1200	5,15	7		
	HT4723	13	3.43	160	2320	950	3,97	5,4		
		23	6.07	160	2320	1450	7,35	10		
19		5	160	2320	1200	5,8	7,9			
		15	3.96	160	2320	950	4,58	6,23		

66.HT series	HT6628	28	7.4	250	3600	1750	13,38	18,2	18,5	340,5x248,5x159,5
		19	5	250	3600	1200	9,07	12,33		
		15	3.96	250	3600	950	7,35	10		
	HT6639	39	10.3	200	2900	1750	14,7	20		
		32	8.45	200	2900	1450	12,2	16,6		
	HT6646	46	12.15	170	2465	1750	14,7	20		
	38	10.04	200	2900	1450	14,51	19,74			

69.HT series	HT6968	68	18	80	1160	1000	11,02	15	25,8	360x300x210
---------------------	--------	----	----	----	------	------	-------	----	------	-------------

76.HT series	HT7680	80	21.1	100	1450	1000	14,7	20	40	396x356x240
---------------------	--------	----	------	-----	------	------	------	----	----	-------------



63.HT series



47.HT series



66.HT series



69.HT series



76.HT series