

CO₂
H₂S
Cl₂
NH₃
O₃
CO
O₂
CH₄
SO₂
CO₂
H₂S

Triple Plus+

Portable Monitor Oxygen, Toxic and Flammable Gases



Triple Plus+

With over 60,000 units in use worldwide, our customers have come to depend on the robust and reliable performance of the Triple Plus+.

The extremely durable Triax™ case and internal construction makes the Triple Plus+ an industry favourite known for the ability to withstand even the most demanding of applications.

Benefits

- Simple customisation to alternative flammable gas correction factors
- Wide range of sensor types allowing 4 gas detection
- QuickCal – simple rapid calibration
- Peak hold capability for pre-entry checks

Convenient and simple to use

- Large four channel simultaneous gas display
- Piercing 85dBA @ 1m
- Ultra bright LED alarms with top visibility
- Confidence blip, low battery and TWA warnings
- Simple Windows™ software interface

Triple Plus+ features:

Rugged construction

- Triax™ casing will not crack or shatter when dropped
- Unique internal design will resist the harshest treatment
- Full buoyancy makes recovery from water possible

Flexible

- Available for diffusion, manual aspiration or pumped sampling
- Interchangeable sensor modules
- Comprehensive datalogging with site and user names



Triple Plus+

Triple Plus+ is a 4 gas personal monitor for oxygen, toxic and flammable gases used for personal safety around the globe.

Gases and Ranges

Ranges and alarms may vary by country and application which may be configured as required. Each channel can have up to three levels of alarm, including short and long TWA exposure levels for Toxic channels.

A choice of 12 flammable correction factors are available via Portables PC.

Other sensors may be available.

| Gas | Range | Typical Alarm (UK) |
|--------------------------------|------------|--------------------|
| Flam | 0-100% LEL | 20% LEL |
| H ₂ (electrochem) | 0-100% LEL | 20% LEL |
| CH ₄ | 0-100% vol | - |
| O ₂ | 0-25% | 19%/23% |
| H ₂ S | 0-50ppm | 5ppm |
| CO | 0-500ppm | 30ppm |
| SO ₂ | 0-10ppm | 1ppm |
| Cl ₂ | 0-5ppm | 0.5ppm |
| NO ₂ | 0-10ppm | 1ppm |
| PH ₃ | 0-2ppm | 0.1ppm |
| NH ₃ * | 0-50ppm | 25ppm |
| H ₂ (non-Flammable) | 0-2000ppm | N/A |
| HCN | 0-25ppm | 10ppm |
| HCl | 0-10ppm | 1ppm |
| F ₂ | 0-10ppm | 1ppm |
| HF | 0-10ppm | 2ppm |
| ETO | 0-10ppm | 5ppm |
| ClO ₂ | 0-1ppm | 0.1ppm |
| NO | 0-100ppm | 25ppm |

*Unpumped units only

Charging Options

The Triple Plus+ has two dual rate charging solutions supplied with UK, EU, US plug and without plug configurations. A vehicle adapter for in-vehicle charging is also available.

- Standard drop in charging cradle
- PC interface charger



NEW LIBRA Li-Ion Battery Pack

Available in new builds from the 1st March, the new LIBRA battery pack offers extended lifetime and charge cycles. Also designed to replace lead acid batteries in existing units, the LIBRA has solved the reduced lifetime effects of changes in Lead Acid technology during recent years. Compatible with Triple Plus+ and Triple Plus+ IR units whilst maintaining certification levels, the LIBRA charges with the existing charger units and takes only seconds to replace.



Specification

| | |
|---|---|
| Weight | 880 g (1.9 lb) |
| Dimensions | 118 x 200 x 73mm (h x w x d) (4.65 x 7.8 x 2.9 inches) including strap hooks |
| Approval Codes <i>Europe</i> <i>North America</i> | ATEX II 2G: Ex ib d IIC T4 Gb Class I Division 1, Groups A, B, C, D (Lead Acid only) |
| Safety Standards <i>Europe</i> <i>North America</i> | EN50014, EN50020, 94/9/EC, SFA3009, EN50081-2, EN50270, EN50082-2 UL 913, CSA 22.2 No.157 |
| Ingress Protection | IP65 |
| Typical response times | Methane 20 s, Oxygen 10 s, Typical Toxic Gas 20 s |
| Expected sensor life | Flammable 5 years, Toxic 3 years, Oxygen 2 years |
| Audible Alarms | Piercing, rapid intermittent, piezo-electric tone, 85 dBA at 1 m Confidence blip (selectable) Distinctive double blip for low battery with user accept |
| Visible Alarms | Ultra bright flashing red LED in gas hazard Slow flashing green LED indicates instrument is working Distinctive double flash of green LED indicates low battery |
| Display | 2 lines of 24 characters, dot matrix high contrast LCD with back light operating for 30 minutes. Values and units for up to 4 gases displayed simultaneously at current, TWA or peak levels. Low battery, pump failure, real time and elapsed time, calibration and configuration data also displayed |
| Datalogging | Adjustable sample rate, 100 hours @ 1 minute sample rate (maximum 6000 data points per channel), logging of events, user and site |
| NEW LIBRA | Li-Ion rechargeable battery pack Battery Life: Standard instrument >12 hours Pumped instrument >10 hours ATEX and IECEx versions |
| Lead Acid Battery | Lead Acid technology Battery Life: Standard instrument - 12 hours Pumped instrument - 10 hours UL only (LIBRA pending) |
| Battery Charging | Dual rate 'drop in' charger Dual rate charger/PC interface |
| Electric pump | Optional internal pump with on/off button |
| Operating Temp. Range | -20°C to +50°C (-4°F to 122°F) |
| Humidity | 20-90% RH non-condensing |
| PC Interface | RS232 connection via the interface charger. RS232/USB converter available. Portables PC also controls datalogging, giving the user a choice of direct graphical output or a datafile compatible with all leading spreadsheets |
| Calibration | Triple Plus+ can be routinely calibrated using Portables PC software or Crowcon Checkbox IMH |
| Accessories | Supplied as standard: manual, shoulder strap and allen keys (pumped units include additional flow plate, 2m hose and pouch) |
| Optional Accessories | Leather carry case, straight and telescopic probes, water trap, baffle plate, aspirator, calibration flow adaptor and hose |



Thank you for reading this data sheet.

For pricing or for further information, please contact us at our UK Office, using the details below.



UK Office

Keison Products,

P.O. Box 2124, Chelmsford, Essex, CM1 3UP, England.

Tel: +44 (0)330 088 0560

Fax: +44 (0)1245 808399

Email: sales@keison.co.uk

Please note - Product designs and specifications are subject to change without notice. The user is responsible for determining the suitability of this product.