



BAROCAP® Digital Barometer PTB210



Features

- 500 ... 1100 hPa or 50 ... 1100 hPa pressure ranges with serial output
- Different scalings between 500 ... 1100 hPa with analog output
- Electronics housing IP65 protected against sprayed water
- Accurate and stable measurement
- Traceable calibration (certificate included)

Vaisala BAROCAP® Digital Barometer PTB210 is a reliable outdoor barometer for harsh conditions.

For Harsh Environments

PTB210 is ideal for outdoor installations and harsh environments. PTB210 is designed to operate in a wide temperature range, and the electronics housing provides IP65 (NEMA 4) standardized protection against sprayed water.

PTB210 is ideal for use in applications such as weather stations, data buoys and ships, airports, and agrology. They are also an excellent solution for monitoring barometric pressure in industrial equipment such as laser interferometers and engine test benches.

Several Pressure Ranges

PTB210 is designed for various pressure ranges. They are available in two basic configurations:

- Serial output for 500 ... 1100 hPa
- Serial output for 50 ... 1100 hPa
- Analog output with different scalings between 500 ... 1100 hPa

Accurate and Stable Measurement

PTB210 is digitally adjusted and calibrated by using electronic working standards. A higher accuracy barometer, that is fine-tuned and calibrated against a high-precision pressure calibrator, is available for the 500 ... 1100 hPa pressure range.

In addition, PTB210 integrates directly with Vaisala Static Pressure Head Series SPH10/20. This pairing offers accurate measurement in all wind conditions.

Vaisala BAROCAP Technology

PTB210 uses the Vaisala BAROCAP sensor, a silicon capacitive absolute pressure sensor developed by Vaisala for barometric pressure applications. The Vaisala BAROCAP sensor provides excellent hysteresis and repeatability

characteristics and outstanding temperature and long-term stability. PTB210 is delivered with a traceable factory calibration certificate.



PTB210 paired with SPH10 static pressure head

Technical Data

Measurement Performance

Pressure Range

Serial output	500 ... 1100 hPa 50 ... 1100 hPa
Analog output	500 ... 1100 hPa 600 ... 1060 hPa 800 ... 1060 hPa 900 ... 1100 hPa

Serial Output (Units in hPa), Accuracy

Pressure range	500 ... 1100		50 ... 1100
	Class A	Class B	

Non-linearity¹⁾ ± 0.10 ± 0.15 ± 0.20

Hysteresis¹⁾ ± 0.05 ± 0.05 ± 0.10

Repeatability¹⁾ ± 0.05 ± 0.05 ± 0.10

Calibration uncertainty²⁾ ± 0.07 ± 0.15 ± 0.20

Accuracy at +20 °C (+68 °F)³⁾ ± 0.15 ± 0.20 ± 0.35

Temperature dependence⁴⁾ ± 0.20 ± 0.20 ± 0.40

Total accuracy -40 ... +60 °C (-40 ... +140 °F)³⁾ ± 0.25 ± 0.30 ± 0.50

Long term stability (hPa/year) ± 0.10 ± 0.10 ± 0.20

Analog Output, Accuracy

Non-linearity¹⁾ ± 0.20 hPa

Hysteresis¹⁾ ± 0.05 hPa

Repeatability¹⁾ ± 0.05 hPa

Calibration uncertainty²⁾ ± 0.15 hPa

Accuracy at +20 °C (+68 °F)³⁾ ± 0.30 hPa

Temperature dependence⁴⁾ ± 0.50 hPa

Total accuracy -40 ... +60 °C (-40 ... +140 °F)³⁾ ± 0.60 hPa

Long term stability ± 0.10 hPa/year

1) Defined as the ±2 standard deviation limits of end point non-linearity, hysteresis error, or repeatability error.

2) Defined as ±2 standard deviation limits of inaccuracy of the working standard including traceability to international standards.

3) Defined as the root sum of the squares (RSS) of end point non-linearity, hysteresis error, repeatability error, and calibration uncertainty at room temperature.

4) Defined as ±2 standard deviation limits of temperature dependence over the operating temperature range.

Operating Environment

Operating temperature -40 ... +60 °C (-40 ... +140 °F)

Operating humidity Non-condensing

EMC compliance EN61326-1, Generic Environment

Mechanical Specifications

Housing material PC Plastic

IP rating, electronics IP65 (NEMA 4)

IP rating, sensor IP53

Instrument weight 110 g (3.9 oz)

Cable weight 28 g/m (1.0 oz)

Inputs and Outputs

Serial Output

Shutdown ON/OFF

Settling time at startup 2 s

Serial I/O RS-232C
RS-232C /TTL (optional)
RS-485, non isolated (optional)

Parity None, even, odd

Data bits 7, 8

Stop bits 1, 2

Baud rate 1200, 2400, 4800, 9600, 19200

Response time 1 s

Resolution 0.01 hPa (1 measurement/s)
0.03 hPa (10 measurements/s)

Current consumption, normal mode < 15 mA (factory setting)

Current consumption, power down mode < 0.8 mA

Current consumption, shutdown mode 0.2 mA

Analog Output

Outputs 0 ... 5 VDC, 0 ... 2.5 VDC (order specified)

Shutdown ON/OFF

Response time 500 ms

Resolution 300 µV

Measurement rate 3 measurements/s

Current consumption, normal mode < 8 mA

Current consumption, shutdown mode 0.2 mA

All Models

Max. pressure 5 000 hPa abs.

Pressure connector M5 (10-32) internal thread

Pressure fitting Barbed fitting for 1/8 in I.D. tubing

Supply voltage (reverse polarity protected), with RS-232/TTL output 5 ... 28 VDC

Supply voltage (reverse polarity protected), with RS-485 or analog output 8 ... 18 VDC

