

Errors and omissions accepted. Specifications and data subject to change without notice. / Irrtümer und Auslassungen vorbehalten

Description	Beschreibung
Material	Material
Treatment	Behandlung

Cellulose / synthetic • Zellulose / synthetisch
Nanofiber • Nanofaser

Specification	Spezifikation
---------------	---------------

Weight gram/m2	Gewicht Gramm/m2	110
Air perm. m3/m2/hour @200Pa	Luftdurchl. m3/m2/Stunde	702
CFM	CFM	26
Filter Efficiency	Filter Effizienz	IFA • Class/Klasse: M
Thickness mm	Dicke mm	0.633
Max. continuous operating temp. °C/°F	Max. Dauerbetriebstemperatur °C / °F	80 / 175

Chemical resistance	Chemische Beständigkeit
---------------------	-------------------------

Oil/water	Öl/Wasser	*
Hydrolysis	Hydrolyse	**
Acid	Säure	*
Alkali	Alkali	*
Dust release	Staubabgabe	****

* Fair
 ** Good
 *** Very good
 **** Excellent
 PTFE = Media coated on the outside
 ePTFE membrane = Media contains a membrane. Most dust resistant solution available

* Mäßig
 ** Gut
 *** Sehr gut
 **** Hervorragend
 PTFE = Medium mit Außenbeschichtung
 ePTFE-Membran = Medium enthält eine Membran – die derzeit staubbeständigste Lösung

