

Mechanical data	
Enclosure	AL, die-cast
Protective guard (Accident protection cover UN)	AL, die-cast
Actuatore	Foot level (PA)
Ambient air temperature	-30 °C ... +80 °C
Contact type	1 N.C, 2 N.O (Zb)
Shifting force	approx. 10 N (pedal centre)
Pressure point	approx. 200 N
Mechanical life	1 x 10 ⁶ operating cycles
Switching frequency	max. 50/min
Assembly	2 x M8
Connection	Screw terminals (M3,5)
Number of connections	6 (see switching symbols)
Protection ground	2 x M4
Conductor cross-sections	Solid: 0,5 – 1,5 mm ² Wire with ferrules: 0,5 – 1,5 mm ²
Cable entry	2 x M20 x 1,5; 1 x tight cable gland M20 x 1,5 (tightness-range 6-12 mm)
Weight	approx. 1,5 kg
Protection type	IP65 in accordance with IEC/EN 60529
ID for safety engineering	
B10d	2 x 10 ⁶ switching cycles
Regulations	
	VDE 0660 T100, DIN EN 60947-1, IEC 60947-1 VDE 0660 T200, DIN EN 60947-5-1, IEC 60947-5-1
EU Conformity	
	acc. to directive 2006/42/EC
Approvals	
	DGUV cCSA _{US} , A300 (same polarity) CCC
Safety function	
<p>Three stage safety footswitch with latch</p> <p>The safety footswitch contacts are wired in series, this allows normal machine operation with the advantage of a safety latched „Emergency stop” if the pedal is fully depressed.</p> <ol style="list-style-type: none"> 1. Rest-Machine stopped. 2. Machine start is enabled by depressing pedal to the pressure point, this closed the normally open contacts 43-44 and 13-14. 3. In an emergency, the pedal is fully depressed (beyond the pressure point). The normally closed contacts 35-36 are force disconnected stopping the machine, simultaneously the latch engages and holds the contacts in this “Emergency stop” status, preventing an unauthorised re-start of the machine. <p>„Safety for man and machine“</p> <ol style="list-style-type: none"> 3. Only after releasing the latch, by pressing the push button mounted in the side of the footswitch body, do the contacts reset allowing normal operation to resume. 	
Notes	
<p>The specified protection classification (IP code) applies only when the cover is closed and the appropriate cable is used, in accordance with the clamping range of the above mentioned cable gland.</p>	

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Date of issue 04.12.2012 / Blatt 2 von 2
Document: 6161000560_en / Status : 2 / 2522-12