



1-095 Quarter-Turn Polyamide Pr20.1 L18



Advantages

- For cutout Pr20.1.
- Protective insulated.
- IP65/67 according to DIN EN 60529 (optional).
- RH / LH application.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.
- When using inserts zinc die + cams stainless steel or inserts stainless steel + cams stainless steel, electrical continuity can be ensured by means of the grounding clip.

Materials

- **Housing and cams:** PA, black
- **Nut:** see table

Remarks

(S) Door-thickness max. 8mm
Please configure the quarter-turn with insert and cam.
Pre-assembling by DIRAK is advisable.



Quarter-Turn housing + nut

	Part Number	Version	Material nut	Installation type	Delivery Unit
a)	200-9044.00-00000	housing head frustoconical	stainless steel	screw-on	10 pcs.

Function



extension

- f) 200-1101.04-00000 **Grounding clip**
- e) 209-9001.00-00000 **Sealing kit IP67 for Quarter-Turns Pr20.1**
- e) 209-9002.00-00000 **Sealing kit IP65 for Quarter-Turns Pr20.1**



Assembly options

- 200-0001.00-00000 **Assembling cam without o-ring**
- 200-0002.00-00000 **Assembling cam with o-ring**
- 200-0006.00-00000 **Assembling cam 90° to wing knob without o-ring**
- 200-0007.00-00000 **Assembling cam 90° to wing with o-ring**

***** Accessories

- c) 1-101 **Inserts Pr20.1**
- c) 7-082 **Insert Stainless Steel Pr20.1**
- d1) 1-102 **Cams L35/45 Steel**
- d1) 7-105 **Cams L35/45 Stainless Steel**
- 6-100 **Wrenches and Keys**
- 6-101 **Universal key**

