

Ventilazione Protezione	<i>Cooling</i> <i>Protection</i>	IC06-IC17-IC37 IP23	ML 100
Velocità massima meccanica	<i>Maximum mechanical speed</i>		
Massa	<i>Mass</i>	55,5 / 66 / 77 / 88 Kg	

Tipo Type	Corrente di Armatura <i>Armature current</i>					Potenza Power KW	Velocità' Speed rpm	Coppia Torque Nm	P eccitaz. excitation Watt	Rendimento Efficiency %	Inerzia Inertia Kgm2
	170V	260V	280V	400V	440V						
ML100 S	19.4	12.7	11.8			2.94	1000	28	300	88	0.0305
	29	19	17.6	12.3	11.2	4.4	1500				
	38.7	25.3	23.5	16.5	15	5.88	2000				
	48.4	31.7	29.4	20.6	18.7	7.35	2500				
		38	35.3	24.8	22.5	8.82	3000				
ML100 M	27.2	17.8	16.5			4.16	1000	40	400	89	0.038
	40.8	26.7	24.8	17.4	15.8	6.25	1500				
	54.4	35.5	33	23.1	21	8.33	2000				
		44.5	41.3	28.9	26.3	10.5	2500				
			49.5	34.7	31.5	12.5	3000				
ML100 L	31.7	20.8	19.3	13.5	12.3	4.9	1000	47	500	90	0.0462
	47.6	31	28.9	20	18.4	7.35	1500				
		41	38.5	27	24.5	9.8	2000				
		52	48	33.7	30.6	12.25	2500				
			40.5	36.8	36.8	14.7	3000				
ML100 P	39.5	25.8	24	16.7	15.2	6.12	1000	58.5	600	90.5	0.0537
		38.7	35.9	25.2	22.9	9.2	1500				
		51.6	47.9	33.6	30.5	12.2	2000				
				41.9	38.1	15.3	2500				
				50.3	45.7	18.3	3000				

Ventilazione Protezione	<i>Cooling</i> <i>Protection</i>	IC06-IC17-IC37 IP23	ML 112
Velocità massima meccanica	<i>Maximum mechanical speed</i>		
Massa	<i>Mass</i>	100 / 110 / 120 / 135 Kg	

Tipo Type	Corrente di Armatura <i>Armature current</i>					Potenza Power KW	Velocità' Speed rpm	Coppia Torque Nm	P eccitaz. excitation Watt	Rendimento Efficiency %	Inerzia Inertia Kgm2
		260V	280V	400V	440V						
ML112 S		26.4	24.5	17	15.6	6.12	1000	58.5	540	88	0.074
		39.6	36.7	25.7	23.4	9.2	1500				
		52.8	49	34.3	31.2	12.2	2000				
		66	61.2	42.9	39	15.3	2500				
			73.5	51.4	46.8	18.3	3000				
ML112 M		31.4	29.1	20.4	18.54	7.35	1000	70	640	89	0.086
		47.1	43.7	30.6	27.8	11	1500				
		62.7	58.3	40.8	37.1	15	2000				
		78.4	72.8	51	46.3	18.3	2500				
			61.2	55.6	61.2	22	3000				
ML112 L		36.3	33.7	23.6	21.4	8.57	1000	82	740	90	0.097
		54.4	50	35.4	32	12.8	1500				
		72.5	67.4	47.2	43	17	2000				
			84.2	58.9	53.5	21.5	2500				
				79.7	64.3	25.7	3000				
ML112 P		40.7	37.8	26.5	24	9.8	1000	93.5	840	92	0.109
		61	56.7	39.7	36	14.7	1500				
		81.5	75.6	52.9	48	19.6	2000				
				66.3	60	24.5	2500				
				79.5	72	29.5	3000				